

Its best feature: unmatched versatility

A 4K UHD digital whiteboard that adds versatility to healthcare

The Samsung WMB series digital whiteboard can enhance your level of care in so many areas. It's ideal for multimedia presentations and collaborative meetings, whether in-person or remote. Add the rolling stand (55" WMB) and it's a mobile signage board, a children's art palette or a senior living residence dance instructor. The WMB series can be whatever you, your staff, your visitors or your patients need it to be.



Improve care in so many ways

Annotate and collaborate in real time

Make every conference room and huddle room an interactive meeting space. With Cisco Webex, team members can collaborate either in person or remotely.



Add the optional rolling stand to the 55" WMB, and you have a signage solution for a pop-up COVID testing site or immunization clinic. You can display pre-check in directions, a reminder to wear a mask and more.



Let patients or residents create artwork, then print or email them to family and friends. Host an impromptu movie matinee. Allow family and friends to visit virtually. Set up a virtual fitness instructor for your residents. And so much more.







Samsung Interactive Displays	WM55B	WM65B	WM75B	WM85B
K UHD Resolution	✓	✓	✓	✓
	✓	✓	✓	✓
Shatter-Resistant Screen ¹	✓	✓	✓	✓
Antimicrobial-Coated Screen ²	✓	✓	✓	✓
Palm Erase	✓	✓	✓	✓
Brush Mode	✓	✓	✓	✓
Cisco Certified	✓	✓	✓	✓
Miracast	✓	✓	✓	✓
ogitech Compatible	✓	✓	✓	✓
Multi-Device Mirroring			✓	✓
Airplay	✓	✓	✓	✓
RMS (Remote Management System)	✓	✓	✓	✓
)PS			✓	✓
Havrion Emergency Response			✓	✓
Varranty	3 years (2 years extended option available)	3 years (2 years extended option available)	5 years	5 years

Full-featured flexibility



Responsive and intuitive touch

Exceptionally responsive touch displays enable staff members and patients to write and draw smoothly and naturally. Flexible erasing requires just a swipe of a finger or palm. And multi-touch allows multiple users to simultaneously write or draw on the display for enhanced collaboration.



Best-in-class annotation

Take notes. Highlight critical details. Your team can annotate onto photos, documents, web browsers and applications, then save and share.



Antimicrobial coating and shatterresistant glass

The screen surface of the WMB series is treated with an antimicrobial coating,¹ while shatter-resistant glass helps reduce hazards.²



Multiple virtual conferencing options

The WMB series offers multiple ways to host meetings, allows virtual visiting between patients or residents and family, and more. Access Cisco WebEx® with a simple tap on the display's screen. And with Logitech device compatibility, you can easily use your Zoom and Teams apps.³



Start meetings faster with USB-C

Users can simply connect their device to the USB-C port to start sharing content without any hassle. In addition to fast data, audio, video transfer and touch control, USB-C also provides 65W external device charging.



Multi-device casting for enhanced collaboration

With SmartView+ you can mirror up to four devices to the display simultaneously, regardless of OS³: Android, Chrome, iOS or Windows. Bidirectional communication allows you to the display's content from any connected device, as well as annotate a device's content right on the display.



Connect with Airplay 2

Effortlessly share or mirror almost anything from your iOS device or Mac directly to the WMB Interactive Display.³



Manage from anywhere, update on the fly

Centrally manage your interactive displays, update firmware and send out notifications with MagicINFO Remote Management solution.⁴



Emergency alerts

Use MagicINFO to create emergency notifications, such as evacuation instructions customized to each display location. Havrion Protect³ software integrates with your existing emergency monitoring systems to automatically broadcast your messages in an emergency.



Up to 5-year warranty

A 5-year parts and labor warranty on the 75" and 85" models, and a 3-year warranty on the 55" and 65" models with the option to extend it an additional two years, leaves you free to worry about more important things.





Accessories



Rolling Stand

55"

STN-WM55R

Have impromptu meetings anywhere. Turn any area into an entertainment area for kids or seniors. Set up mobile digital signage where you need it.



Connectivity Tray

55" and 65" CY-TF65BR

Easily add multiple connections for increased versatility.



OPS Box

75", 85" CY-PBRK200

An OPS box lets you use third-party apps and tools.



Wall Mounts

55": WMN-4277SF

65": WMN-WM65R

75": WMN6575SF

85": WMN8200SF

A wall mount can save space and give a cleaner overall appearance.



CY-PENR

Two pens are included with each WMB display. For even greater collaboration, have additional pens on hand.

Connectivity

- Optional Tray
- Service
 HDMI1
- DisplayPort
 Touch Out
- 7. Audio Out8. OPS SLOT

Front

2. LAN







Connectivity Tray (CY-TF65BBC)

USB In (External)

9. USB

- 11. USB Out (External)
- 12. Touch Out 2

- 13. HDMI 2
- 14. USB-C (without P/D)



			WM55B	WM65B	WM75B	WM85B
	Diagonal Size		55"	65"	75"	85"
	T a				N=Ed== (011=	
	Desclution		New Edge, 60Hz 3,840 x 2,160 (Landscape)	New Edge, 60Hz 3,840 x 2,160 (Landscape)	New Edge, 60Hz 3,840 x 2,160 (Landscape)	New Edge, 60Hz 3,840 x 2,160 (Landscape)
1	Deighte and (Top.)		3,040 X 2,100 (Latituscape)	750 = it= (with sut alass)	7.00 - it- (with sut alass)	3,040 x 2,100 (Lanuscape)
nel	Brightness (Typ.)		350 nits (without glass)	350 nits (without glass)	350 nits (without glass)	350 nits (without glass)
	Contrast Ratio (Typ.)		4000:1 (Typ.) (without glass)	4000:1 (Typ.) (without glass)	4700:1 (Typ.) (without glass)	4700:1 (Typ.) (without glass)
	Viewing Angle (H/V)		178° (H) /178° (V)	178° (H) / 178° (V)	178° (H) /178° (V)	178° (H) / 178° (V)
	Response Time (G-to-	G)	8ms (Typ.)	8ms (Typ.)	6ms (Typ.)	6ms (Typ.)
peration Hours			16/7	16/7	16/7	16/7
ound	Speaker Type		Built in Speaker (10W x 2) (Basic) HDMI1, DP1 (With Tray) HDMI1, USB-C	Built in Speaker (10W x 2) (Basic) HDMI 1, DP1 (With Tray) HDMI 1, USB-C	Built in Speaker (10W x 4)	Built in Speaker (10W x 4) HDMI 2 (Rear1, Front 1), DP1, USB C (Front), OPS I/F
		Video	(Basic) HDMI 1, DP1 (With Tray) HDMI 1, USB-C	(Basic) HDMI1, DP1 (With Trav) HDMI1, USB-C	HDMI 2 (Rear 1, Front 1), DP1, USB C (Front), OPS I/F	HDMI 2 (Rear1, Front 1), DP1, USB C (Front), OPS I/F
	Input	LISB	(Basic) USB1 (With Tray) USB 2, USB External (In / Out) 1	(Basic) USB1 (With Tray) USB 2, USB External (In / Out)1	2 (For SoC, Rear / Front), 1 (for external 3.0x1 (Front))	2 (For SoC, Rear / Front), 1 (for external 3.0x1 (Front))
		Audio	1 (Stereo Mini Jack)	1 (Stereo Mini Jack)	1(Stereo Mini Jack)	1 (Stereo Mini Jack)
onnectivity	Output		(Basic) Touch Out 1 (USB Upstream Type)	(Basic) Touch Out 1 (USB Upstream Type)		
Jillectivity	Output	Touch Out	(With Tray) Touch Out 1	(With Tray) Touch Out 1	Touch Out 2 (USB Upstream Type, Front 1, Rear1)	Touch Out 2 (USB Upstream Type, Front 1, Rear 1)
	External	Control	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)
		Control				
	Bluetooth / Wi-Fi		Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)
	Туре		IR IR	IR .	IR	IR .
	Number of Drawing		Multi-Annotation up to 4	Multi-Annotation up to 4	Multi-Annotation up to 4	Multi-Annotation up to 4
	Touch Pen Type		Passive Pen with Magnet	Passive Pen with Magnet	Passive Pen with Magnet	Passive Pen with Magnet
			2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm
	Object Recognition R	ange	(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)
	Touch Response Time			(Drush Mode: Dynamic Object Recognition)		
			6.7ms	6.7ms	6.7ms	6.7ms
	Drawing Speed (Touch	latency)	26ms	26ms	26ms	26ms
	Haze		8%~12%	8%~12%	8%~12%	8%~12%
	Thickness		2.85T	3.2T	3.2T	3.2T
	Hardness		Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass
			AG Film (Anti glare) Hydrophobic Coated PET	AG Film (Anti glare) Hydrophobic Coated PFT	AG Film (Anti glare) Hydrophobic Coated PET	AG Film (Anti glare) Hydronhobic Coated PET
	Additional Film		AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating
	Type		Internal	Internal	Internal (Main1ea, OPS1ea)	Internal (Main 1ea, OPS 1ea)
	Type Comple		AC100-240V 50/60Hz	AC100-240V 50/60Hz	AC100-240V 50/60Hz	AC100-240V 50/60Hz
PowerSupply	PowerSupply	1			AC100-240V 50/60HZ	
		Max (W/h)	154W (100-240V)	192.5W (100-240V)	473W (100-240V), 451W(220-240V), OPS (16V/4.5A)	528W (100-240V), 506W (220-240V), OPS (16V/4.5A)
ver	Power	Typical (W/h)	95W	124W	187W	197W
	Power Consumption	Rating (W/h)	140W	175W	430W (100-240V), 410W (220-240V), OPS (16V/4.5A)	480W (100-240V), 460W (220-240V), OPS (16V/4.5A)
	Consumption	Stand-by (W/h)	0.5	0.5	0.5	0.5
		BTU (W/h)	525.14W	656,425W	1612.93W (100-240V), 1537.91W (220-240V), OPS (16V/4.5A) 1724mm x 1026.3mm x 89mm / 67.87" x 40.41" x 3.5"	1800.48W (100-240V), 1725.46W (220-240V), OPS (16V/4.5A) 1945.8mm x 1151.1mm x 89mm / 76.61" x 45.32" x 3.5"
		Set	1297.4mm x 768.2mm x 59.9mm/ 51.16" x 30.24" x 2.36"	1522.4mm x 897.6mm x 62.9mm / 59.94" x 35.34" x 2.48"	1724mm v 1026 3mm v 89mm / 67.87" v 40.41" v 3.5"	19/15 8mm v 1151 1mm v 89mm / 76 61" v /15 32" v 3 5"
	Dimensions	Package	1464mm x 915mm x 190mm / 57.64" x 36.02" x 7.48"	1691mm x 1055mm x 198mm / 66.57" x 41.54" x 7.8"	1905mm x 1189mm x 287mm / 75" x 46.81" x 11.3"	2136mm x 1318mm x 260mm / 84.09" x 51.89" x 10.24"
Weight		Package		39.7 kg / 87.5 lbs.		213011111 X 131011111 X 200111111 / 04.09 X 31.09 X 10.24
	Weight	Set	28.6 kg / 63.1 lbs.		59.3 kg / 130.7 lbs.	75.2 kg / 165.8 lbs.
		Package	35.9 kg / 79.1 lbs.	48.2 kg / 106.3 lbs.	72.2 kg / 159.2 lbs.	91.6 kg / 201.9 lbs.
chanical	Color		Gray White	Gray White	Gray White	Gray White
echanical VESA Mount			400 x 400	400 x 400	400 x 400	600 x 400
Protection (Protection Glass		Yes	Yes	Yes	Yes
	Stand Type (Optional)		Stand / Wall Mount (STN-WM55R / WMN4277SF)	Wall Mount (WMN-WM65R)	Wall Mount (WMN6575SE)	Wall Mount (WMN8200SFXZA)
	Media Player Option T	vne	N/A	N/A	OPS Slot Support	OPS Slot Support
	Potation Potation	7 PC	Landscape / Portrait	Landscape / Portrait	Landscape only	Landscape only
	Rotation Payment		3M/2.4M	3M / 2.4M	3M /2.4M	3M /2.4M
	Power Cable Length		0°C~ 40°C / 32°F~104°F	0°C~ 40°C / 32°F ~ 104°F	0°C~ 40°C / 32°F ~ 104°F	0°C~40°C / 32°F~104°F
eration	Operating Temperature Humidity	е				
	Humidity		10~80%, Non-condensing	10~80%, Non-condensing	10~80%, non-condensing	10~80%, non-condensing
	Key		Flip App	Flip App	Flip App	Flip App
	Orientation		Landscape / Portrait	Landscape / Portrait	Landscape	Landscape
			Touch module (IR), Built in Speaker (20W 2CH), WiFi / BT Module	Touch module (IR), Built in Speaker (20W 2CH), WiFi / BT Module	Touch Overlay (IR), Front Connectivity, OPS I/F Support (w/OPS Box), Built in Speaker (40W 4CH), WiFi / BT Module Embedded	Touch Overlay (IR), Front Connectivity, OPS I/F Support (w/OPS B Built in Speaker (40W 4CH), WiFi / BT Module Embedded
H	Hardware		Embedded	Embedded	Built in Speaker (40W 4CH), WiFi / BT Module Embedded	Built in Speaker (40W 4CH), WiFi / BT Module Embedded
		First screen	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)
		- macacreen				
		Apps	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare)	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare)	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare)	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare),
		Apps	Workspace, (RDP / VNC, Office365, VMWare)	Workspace, (RDP /VNC, Office365, VMWare)	Workspace, (RDP /VNC, Office365, VMWare)	Workspace, (RDP /VNC, Office365, VMWare),
ture	Software	WebDTC				
		WebRTC	Yes	Yes	Yes	Yes
		Upgradable web engine	Yes	Yes	Yes	Yes
		Smartview+	Yes	Yes	Yes	Yes
		Airplay	Yes	Yes	Yes	Yes
		Platform	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)
	Internal Player	Processor	CA72 Quad (1.7GHz)	CA72 Quad (1.7GHz)	Cortex A721.7GHz Quad-Core CPU 2MB L2	Cortex A72 1.7GHz Quad-Core CPU 2MB L2
	Internal Player (Embedded H/W)	Storage	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)
	(Linbedded 11, W)	Operating System	Tizon 4 F: Campung Proprietary OC (VDL inus)	Tizon 4 E: Compune Dropriotopy OC (VDL inus)	Tizon 4 F: Cameuna Droprintary OC (VDL inux)	Tizon 4 F: Cameung Proprietary OC (VD) inus)
ite.		Operating system	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TLS, EAP-PEAP
ırity			802.IX (WPAZ ENTERPRISE): EAP-ILS, EAP-ILS, EAP-PEAP	802.1x (WPAZ ENTERPRISE): EAP-ILS, EAP-ILS, EAP-PEAP	BUZ.IX (WPAZ ENTERPRISE): EAP-ILS, EAP-ILS, EAP-PEAP	8UZ.IX (WPAZ ENTERPRISE): EAP-ILS, EAP-IILS, EAP-PEAP
	Included		Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),
	Interductu		Warranty / Quick Start Guide	Warranty / Quick Start Guide	Warranty / Quick Start Guide	Warranty / Quick Start Guide
		Stand	STN-WM55R	N/A (3rd party stand can be supported through VESA)	N/A (3rd party stand can be supported through VESA)	N/A (3rd party stand can be supported through VESA)
essories		Mount	WMN-4277SF	WMN-WM65R	WMN6575SE	WMN8200SFXZA
	Optional	OPS Mount		-	CY-PBRK200	CY-PBRK200
	optionat	Trav	- CY-TF65BR	CY-TF65BR		
					CV PEND	CV PEND
		Flip Pen	CY-PENR 3 Years (Optional 2 Years Extended Warranty Available)	CY-PENR 3 Years (Optional 2 Years Extended Warranty Available)	CY-PENR 5 Years	CY-PENR 5 Years

Learn More samsung.com/display samsung.com/business insights.samsung.com

Product Support 1-866-SAM4BIZ

Follow Us youtube.com/samsungbizusa @SamsungBizUSA





©2023 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All other brand, product, service names and logos are trademarks of their respective manufacturers and companies. Screen images simulated. Non-metric weights and measurements are approximate. Specifications and designs are subject to change without notice. See samsung.com for detailed information. Printed in USA. DIGSIG-HC-WMB-DSHT-MAR23T